

KEN Dishwashers

KEN Industrial Dishwashers -

designed for any need



For further Information, please visit: www.ken.dk

Recommended by professionals



Professional diswashers assuring quick and high pressure washing. All KEN machines are equipped with automatic monitoring of the washing process. We ensure a high quality and hygienic washing result: All machines are rinsing at 80 degrees C, as requested for restaurants, canteens and institutions.

An costefficient solution due to minimum water and low energy consumption. Easy handling and programming with interface.

KEN DW 330

KEN 330 Standard

KEN Dishwashers are known for high material and functional standards as well as for quality and reliability, The average lifetime of a KEN Dishwasher is remarkably long.

KEN 330 is no exception as it is designed in stainless steel and developed for intensive use 24/7.

KEN 330 is the smallest version of its class. Due to its size, it can be installed in very narrow environments.

KEN 330 washing concept

The washing concept consists of static baskets, while the washing arms are cleaning the kitchenware from beneath and above. After the washing process, special nozzles are rinsing the content from all sides, ensuring a perfect washing result. With an average time of 2 minutes per washing-cycle, KEN 330 easily washes up to 30 baskets per hour.

The entire washing process is electronically monitored by an operating computer, and the display informs the user about irregularities like lack of detergent or water among others.





Dish Washer 330

Technical specifications:

DW 330

-	
Basket Dimensions:	500 x 500 mm
Washing and rinsing system:	Rotating washing and rinsing arms
Water consumption per washing cycle:	3,5 litres
Volume of water reservoir:	12 litres
Min. water pressure:	Built-in water softener: 2 bar -12 litres/min.
	Without water softener: 3 bar - 12 litres/min.
Max. waterpressure:	Built-in water softener: 8 bar
	Without water softener: 5 bar
Capacity washing pump:	370 litres/min 850 W
Power connection (Standard):	3 x 400V+N+J, 50 Hz
Water connection:	3/4* or 1/2* RG. Temp: 50°C, max 65°C
Noise level:	60 db
Programs:	3 Standard programs: 110, 170 and 290 secs.

Malones Hospital Services Pty Ltd. 24 Tathra Street West Gosford, 2250, NSW Phone: +61 (02) 4323 9731 sales@malones.com.au - www.malones.com.au